

Standard Trailer

Steel Control & Battery Boxes

- Lockable
- Metal boxes
- Sealed weatherstripping
- Non-slip treads on top
- Easy control access

Control Panel

- Streamlined instrument layout
- See only the controls you need
- Easy Programming Guide on panel

Standard Display

BRICK® LED Module

- Self-contained, sealed LED unit
- High Density
- No special tools needed
- Plug-and-play simplicity

Legibility & Power Consumption

- Superior legibility
- Automatically adjust LED 0 to 100% brightness for ambient conditions
- Power Management System

Message Display

- 3 lines, up to 12 characters per line
- Variable width fonts

Message Panel

- Aluminum back plate & surround
- Flat black powder coat finish
- Lightweight, wind load tested
- Sealed BRICK® LED modules

Sign Locking

- Heavy-duty brake

Available Options

- Solar Tilt & Rotate (S.T.A.R.)®
- Additional solar panels & batteries
- Radar
- Hydraulic surge brakes
- Deluxe locking lug nuts
- Custom paint colors
- Tongue jack
- Cell modem
- Land line modem
- Extended warranty



Removable Tongue

Trailer Construction & Materials

We are an ISO 9001:2000 certified company. We use exacting standards to develop, engineer and manufacture every product. The quality of materials and dedicated craftsmanship of our trailers give you superior durability, lower total cost of ownership and a better return on investment.

Key features:

- Heavy-duty, Grade B, structural steel tubing
- Steel tubing size: 4" x 2" x 3/16"
- MIG welds
- Highway Safety Orange powder coat finish
- Fenders: Bolt-on, heavy-duty, 10-gauge, steel with non-slip treads
- Torsion axle
- 80" wide footprint
- Removable Tongue

LED Power Management System

Side-by-side competitive comparisons of ADDCO's full matrix displays show the exceptional legibility of our products. Our exclusive Power Management System produces an extremely low drive current while achieving superior legibility at up to 1,200 feet. This technology requires fewer solar panels and batteries and gives you greater autonomy.

Key features:

- Highest intensity LEDs purchased in BIN
- Single color LEDs purchased in BIN
- LED brightness consistent across entire display face
- Amber LED color consistent across entire display face

Specifications

Mid-Size 3-Line

STANDARD CONFIGURATION- DH500-ALS

Trailer Dimensions

Width.....	80"
Length with hitch.....	193"
Length without hitch	109"
Operating height.....	165"
Transport height	108"
Ground clearance.....	10.25"
Gross Weight	2,500 lbs.

Message Panel Dimensions

Height.....	76"
Width.....	134"
Depth	5"

Features

- Best towing trailer
- Removable tongue
- 7-function taillight & amber side marker package meets FMUSS 108 specifications
- 3,500 lb. Dexter torsion axle = independent suspension
- Heavy-duty Tow Master II 50-lb. tires DOT1NVT compliant

Powder Coat Finish

- Highway Safety Orange powder coat

Tower

- Telescoping
- 360° rotation
- Lock in any position

Batteries & Solar Panels


- Battery & Solar Panel configurations are customized for maximum performance in the customer's geographic area

Sign Controller & Software

- EZPro™ Handheld Terminal
- Operate from the clear zone
- Rugged handheld specifically for PCMS applications
- Heavy-duty coiled cord
- Create, edit, display messages with text, graphics or both
- Store up to:
 - 99 operator programmed messages
 - 200 preprogrammed messages
- Easily change messages on the fly
- Displays low battery voltage warning
- Password protected

Warranty

- 1-year warranty on parts and workmanship
- 2-year warranty on BRICK® module, electronic components



ms3l_0608

Specifications are subject to change without notice.

 ADDCO.com